



TWO DOOR CLEAN BENCH



DK-TCB 001

General Features

- **Two Door Type**
This model is for 2 person's working face to face for large capacity working and sequence working.
- **Economical Model**
Space save model, can set many units in the same small space.
- **Utility Device**
110V/220~240V Concent, Gas Cock, Vacuum Cock, Hour Meter.
- **High Efficiency Filter**
Keeping clean space with High Efficiency Main Filter(0.3 μm, 99.99%) and Exhaust-Filter.
- **Vertical Air Flow Type**
Wind is come from the top to the bottom.

Specification

Model	DK-TCB 001	DK-TCB 010
Dimension(IN)	1200 x 800 x 620(H) mm	1800 x 800 x 620(H) mm
Dimension(OUT)	1340 x 850 x 1950(H) mm	1980 x 850 x 1950(H) mm
Illumination(F.L)	40W x 2EA	40W x 3EA
Sterilization(U.V)	30W x 2EA	40W x 2EA
Blower Motor	1/2HP	3/4HP
Main Filter	HEPA Filter(0.3 μm 99.99%)	
Pre Filter	Nylon Filter	
Exhaust Filter	HEPA Filter(0.3 μm 99.99%)	
Purity	Class 100	
Wind Velocity	0.35-0.45m/sec	
Air Volume	22-25m ³ /min	
Material(IN)/(OUT)	Stainless Steel (SUS304) Polishing Plate/ SCP-1 With Powder Coating	
Material(DOOR)	Sliding Door Tempered Glass	
Noise	Less Than 60db	
Utility	Hour Meter, Concent, Gas Cock, Vacuum Cock	
Power(AC 220V, 60HZ)	600W	800W

Option

Model	DK-TCB 001-D	DK-TCB 010-D
Control Type	Full Digital Microprocessor Control LCD Display	



Controller



Inner Shape (DK-HCLB 001)



Pre Filter (DK-LCB 001)



Concent

⚠ The instruments have been tested in 220V, 60Hz power condition.
There can be performance difference according as power condition of each country